



额定载荷 Rated Load(t)	尺寸 (mm) Size									
	D	H	H1	F	L	H3	D2	D1	H2	M0
20	76	82.6	48	150	56	9	31.8	48	10	M12
25	100	117	65	150	76	12	38	38	14	M20
30	100	117	65	150	76	12	38	38	10	M12
40	100	117	65	150	76	12	38	38	14	M20
50, 60	107	127	66	200	81	12.7	58	64	14	M20
70	125	142	91	250	86.5	13	58	64	14	M20
100	165	184	104	300	111.8	20	70	70	20	M20
150	165	184	104	300	111.8	20	70	78	20	M20
200	223	250	152	500	137.5	20	100	112	36	M24
300, 400	223	250	152	500	137.5	20	108	112	36	M24

参数	Specifications	技术指标/Technique
额定容量	Capacity	20,25,30,40,50,60,70,100,150,200,300,400t
输出灵敏度	Rated output	2.0±0.002mV/V
零点输出	Zero balance	±1% F.S.
非线性	Non-linearity	0.03%F.S.
滞后	Hysteresis	0.03%F.S.
重复性	Repeatability	0.03%F.S.
蠕变 (30min)	Creep(30min)	0.03%F.S.
温度灵敏度漂移	Temp.effect on output	0.02%F.S./10℃
零点温度漂移	Temp.effect on zero	0.02%F.S./10℃
输入电阻	Input impedance	400±20Ω
输出电阻	Output impedance	352±3Ω
绝缘电阻	Insulation	≥5000MΩ/100VDC
激励电压	Recommended excitation	5V
最大激励电压	Maximum excitation	15V
温度补偿范围	Compensated temp range	-10~40℃
工作温度范围	Operation temp range	-20~60℃
安全超载	Safe overload	150%F.S.
极限超载	Ultimate overload	200%F.S.
电缆线尺寸	Cable size	Φ8×12000mm
单件重量	Weight approx.	10kg
材料	Material	Alloy Steel (合金钢)
防护等级	IP Class	IP68